



Office of Training  
and Certification

# New Jersey Division of Fire Safety

## BASIC PRACTICAL SKILLS EXAMINATION REPORT

Skill sheet #

**FF1-36**

Certification title

**Firefighter 1**  
**Two-Fire Fighter Flat Raise**

### Applicant Information

Candidate name

DFS ID #

Course #

### Evaluation

**Standard:**  
**NFPA 1001, 2019 Edition**  
**Skill Drill 11-15**  
**Fire Fighter I, 4.3.6**  
**Mandatory**

#### Task

Safely rung raise a ladder with a partner. Two-fire fighter rung raise.

#### Conditions and Outcome

The candidate shall be provided with an extension ladder, personal protective equipment, and a partner. The candidate shall be able to safely rung raise an extension ladder with a partner.

Number	Task Steps	First Test		Retest #1		Retest #2	
		Pass	Fail	Pass	Fail	Pass	Fail
<b>1</b>	The two-fire fighter flat raise begins from a shoulder carry or suitcase carry, with one fire fighter near the butt of the ladder and the other near the tip. The fire fighter at the butt of the ladder places the butt of the lower beam on the ground, while the fire fighter at the tip holds the other end. The fire fighter at the tip rotates the ladder so that both butts are in contact with the ground.						
<b>2</b>	The fire fighter at the butt of the ladder stands on the bottom rung, grasps a higher rung with both hands, crouches down, and leans backward to heel the ladder. The fire fighter at the tip of the ladder checks for overhead hazards, then swings under the ladder and walks toward the butt, advancing down the ladder and lifting the rungs in a hand-over-hand fashion until the ladder is vertical.						
<b>3</b>	The two fire fighters stand on opposite sides of the ladder and pivot it into position as necessary ensuring proper orientation of the ladder.						
<b>4</b>	The fire fighters face each other, one on each side of the ladder, and heel the ladder by each placing the toe or instep of one boot against the opposing beams of the ladder.						
<b>5</b>	If using an extension ladder, one fire fighter extends the fly section by pulling the halyard smoothly with a hand-over-hand motion until the tip is at the desired height and the pawls are locked. The other fire fighter stabilizes the ladder by holding the outside of the base section beams so that if the fly comes down suddenly it will not strike the fire fighter's hands.						
<b>6</b>	The fire fighter facing the structure places one foot against one beam of the ladder, and then both fire fighters lean the ladder into place. The halyard is tied. The fire fighters check the ladder for a 75-degree climbing angle and for stability at the tip and at the butt end of the ladder.						
<b>Final Test Result for Entire Task</b>							

Evaluator signature & comments, Test #1		Evaluator signature & comments, Retest #1		Evaluator signature & comments, Retest #2	
Evaluator signature	Date	Evaluator signature	Date	Evaluator signature	Date
Candidate signature & acknowledgement, Test #1		Candidate signature & acknowledgement, Retest #1		Candidate signature & acknowledgement, Retest #2	
By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments		By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments		By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments	
Candidate signature	Date	Candidate signature	Date	Candidate signature	Date

Form DFS-SS-1 10/12

Approved by NJ SME Committee 11/320/2020