



Office of Training
and Certification

New Jersey Division of Fire Safety

BASIC PRACTICAL SKILLS EXAMINATION REPORT

Skill sheet #

**HM
OPS-05**

Certification title

**Hazardous Materials Operational Level
Donning and Doffing a Level B Non-Encapsulated
Ensemble**

Applicant Information

Candidate name

DFS ID #

Course #

Evaluation

Standard:

NFPA 1072: 6.2.1; NFPA 472: 6.2.1.2.1, 6.2.4.1

Skill Drill 36-3

Skill Drill 36-4

Task

Correctly don and doff a Haz-Mat Level B non-encapsulated chemical protective ensemble.

Conditions and Outcome

Based on which ensemble is available for use, the candidate shall be provided with the appropriate equipment to don and doff a Level B non-encapsulated ensemble. If available, instructors shall place each ensemble out for donning and doffing and assign each crew to complete the task. Students must understand and demonstrate the knowledge of each ensembles and which each level of hazard they are used for.

Number	Task Steps	First Test		Retest #1		Retest #2	
		Pass	Fail	Pass	Fail	Pass	Fail
1	Conduct a pre-entry briefing, medical monitoring, and equipment inspection.						
2	Sit down and pull on the suit to waist level; pull on the chemical boots over the top of the chemical suit.						
3	Don the inner gloves.						
4	With assistance, complete donning the suit by placing both arms in the suit and pulling the suit over your shoulders. Instruct the assistant to close the chemical suit by closing the zipper and sealing the splash flap.						
5	Don the SCBA frame and SCBA face piece, but do not connect the regulator to the face piece.						
6	With assistance, pull the protective hood over your head and the SCBA face piece. Place the helmet on your head. Put on the outer gloves (over or under the sleeves, depending on the AHJ requirements for the incident). Instruct the assistant to connect the regulator to the SCBA face piece, and ensure you have air flow. Review hand signals and indicate that you are okay.						
7	After completing the wash/rinse cycle, proceed to the clean area for PPE doffing. The SCBA frame is removed first. The unit may remain attached to the regulator while the assistant helps the responder out of the PPE, or the air supply may be detached from the regulator, leaving the face piece in place to						

	provide for face and eye protection while the rest of the doffing process is completed.						
--	---	--	--	--	--	--	--

8	Instruct the assistant to open the chemical splash flap and suit zipper.						
9	Remove your hands from the outer gloves and your arms from the sleeves of the suit. Cross your arms in front inside the suit. Instruct the assistant to begin at the head and roll the suit down and away until the suit is below waist level.						
10	Sit down and instruct the assistant to complete rolling down the suit to the ankles; step out of the attached chemical boots and suit.						
11	Doff the SCBA face piece and helmet.						
12	Carefully peel off the inner gloves, and go to the rehabilitation area for medical monitoring, rehydration, and personal decontamination shower.						
Final Test Result for Entire Task							

Evaluator signature & comments, Test #1		Evaluator signature & comments, Retest #1		Evaluator signature & comments, Retest #2	
Evaluator signature	Date	Evaluator signature	Date	Evaluator signature	Date
Candidate signature & acknowledgement, Test #1		Candidate signature & acknowledgement, Retest #1		Candidate signature & acknowledgement, Retest #2	
By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments		By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments		By my signature below I acknowledge I have read and understood the evaluation results and evaluator comments	
Candidate signature	Date	Candidate signature	Date	Candidate signature	Date

Form DFS-SS-1 10/12

Approved by NJ SME Committee 11/25/2020